# GENERAC®

### GP SERIES Commercial/Residential Portable Generators

A/C Rated Output Watts: 17500 A/C Maximum Output Watts: 26250

**GP17500E** 

#### Model 5735-0

UPC Number: 696471057355 Emissions Certification: 49-State



#### features

- GENERAC OHVI ENGINE, FULL PRESSURE LUBRICATION
- HIGH PERFORMANCE ALTERNATOR
- LARGE CAPACITY FUEL TANK FOR EXTENDED RUN TIME
- IDLE CONTROL
- CIRCUIT BREAKER PROTECTED OUTLETS
- BUILT-IN LIFTING EYE.
- HEAVY DUTY, FIXED HANDLES
- 12.3" PNEUMATIC WHEELS
- 1.25" HARDENED STEEL TUBE CRADLE
- LOW TONE MUFFLER

#### customer connections

Connection Outlets


| А | 2X5-20R.GFCI   |
|---|----------------|
| В | (2) 5-20R 120V |
| С | 2xL5-30R       |
| D | 1xL14-30R      |
| Ε | 1x12VDC        |
| F | 1x14-50R       |

#### Circuit Breakers

| Μ | (2) 20A |
|---|---------|
| Ν | (4) 30A |
| 0 | (1) 50A |

Other Features

| Н | Hour Meter          |  |
|---|---------------------|--|
| Ι | Off/On/Start Switch |  |



## specifications

| Product Series             | GP17500E          |
|----------------------------|-------------------|
| Model                      | 5735-0            |
| Configuration/Emissions    | 49-State          |
| A/C Rated Output Watts:    | 17500             |
| A/C Maximum Output Watts:  | 26250             |
| A/C Voltage                | 120/240VAC        |
| A/C Frequency              | 60 Hz             |
| Rated 120/240 VAC Amperage | 72.9              |
| Max 120/240 VAC Amperage   | 109.4             |
| Engine Displacement        | 992cc             |
| Engine Type                | OHVI              |
| Engine RPM                 | 3600              |
| Recommended Oil            | SAE30             |
| Lubrication Method         | Full Pressure     |
| Choke Type                 | Manual Lever      |
| Fuel Shut Off              | Manual Lever      |
| Idle Control               | No Load Low Speed |
| Starting Method            | Electric          |
| Battery                    | Included          |
| Battery Size               | 12VDC 365 CCA     |
| Low Oil Shutdown Method    | Low Pressure      |

| Start Switch Type         | 3-Position              |
|---------------------------|-------------------------|
| Switch Location           | On Engine               |
| Single-Point Lifting Eye  | Included                |
| Fuel Gauge                | Built-in Cap            |
| Fuel Tank Capacity (Gal)  | 16.00                   |
| Fuel Tank Capacity (Ltrs) | 60.56                   |
| Run Time at 50% (Hours)   | 10.00                   |
| Cord Set                  | N/A                     |
| Handle Style              | Fixed                   |
| Wheel type                | 12.3" Phneumatic Wheels |
| Maintenance Kit           | Included                |
| Warranty - Residential    | 2 Year                  |
| Warranty - Commercial     | 1 Year                  |
|                           |                         |

## dimensions and weights

| Length (L)            | 48.5  |
|-----------------------|-------|
| Width (W)             | 30.8  |
| Height (H)            | 38.5  |
| Extended Length (EL)  | 48.5  |
| Carton Length         | 49.3  |
| Carton Width          | 23.3  |
| Carton Height         | 31.0  |
| Unit Weight (Ibs)     | 390.0 |
| Shipping Weight (lbs) | 513.0 |
|                       |       |

