

GP3250

GP SERIES
Commercial/Residential
Portable Generators

GENERAC®

A/C Rated Output Watts: 3250

A/C Maximum Output Watts: 3750

Model 5789-0

UPC Number: 696471057898 Emissions Certification: CARB



features

- OHV ENGINE WITH SPLASH LUBRICATION
- HIGH PERFORMANCE ALTERNATOR
- STEEL FUEL TANK WITH FUEL GAUGE
- FOLD-DOWN HANDLE
- NEVER-FLAT WHEEL KIT
- HARDENED STEEL TUBE CRADLE
- CIRCUIT BREAKER PROTECTED OUTLETS
- LOW TONE MUFFLER
- MEETS EPA, C.A.R.B. AND CITY OF L.A. EMISSIONS

customer connections

Connection Outlets


A 4X5-20R.GFCI

Circuit Breakers

M (2) 13.5A

Other Features

H Off/On/Start Switch



GP3250

specifications

Product Series	GP3250
Model	5789-0
Configuration/Emissions	CARB
A/C Rated Output Watts:	3250
A/C Maximum Output Watts:	3750
A/C Voltage	120 VAC
A/C Frequency	60 Hz
Rated 120/240 VAC Amperage	13.5 @ 120VAC
Max 120/240 VAC Amperage	15.6 @ 120VAC
Engine Displacement	206cc
Engine Type	OHV
Engine RPM	3600
Recommended Oil	SAE 30
Lubrication Method	Splash Sump
Choke Type	Manual Lever
Fuel Shut Off	Manual Lever
Idle Control	Full Speed
Starting Method	Manual
Battery	N/A
Battery Size	N/A
Low Oil Shutdown Method	Low Level

Start Switch Type	On/Off Toggle
Switch Location	On Engine
Single-Point Lifting Eye	N/A
Fuel Gauge	Built-in Tank
Fuel Tank Capacity (Gal)	4.00
Fuel Tank Capacity (Ltrs)	15.14
Run Time at 50% (Hours)	12.50
Cord Set	N/A
Handle Style	Folding
Wheel type	7.0" Solid Wheels
Maintenance Kit	Sold Separately
Warranty - Residential	2 Year
Warranty - Commercial	1 Year

dimensions and weights

Length (L)	23.5
Width (W)	21.0
Height (H)	20.0
Extended Length (EL)	41.5
Carton Length	24.6
Carton Width	18.5
Carton Height	20.0
Unit Weight (lbs)	91.0
Shipping Weight (lbs)	101.5

