



10 ft. hose included



PRODUCT DESCRIPTION:

Provides economical heat to job-sites, tailgating and well ventilated areas. Includes hose and regulator. Use as a 360° heat source with no electricity required.

STANDARD FEATURES:

- Fuel: propane (sold separately)
- BTU: 30,000-80,000
- Heat area: up to 2,000 sq. ft.
- Run time: 14 hours (low setting), 5 hours (high setting)
- No electricity required



Variable output control. Hose and regulator included.

MH80CVX
F270490





CLEARANCE TO COMBUSTIBLES	
Top:	72"
Bottom:	0"
Front:	48"
Back:	48"
Sides:	48"

SPECIFICATIONS

BTU per hour:	50,000 to 80,000
Heating area:	Up to 2,000 sq. ft.
Tank capacity (Min):	20 lbs.
Run time (Hours at max BTU):	5 (20 lbs.)
Run time (Hours at min BTU):	14 (20 lbs.)
Fuel consumption/burn rate (Gal/Hr):	N/A
Electricity required:	No
Maximum elevation:	N/A
Dimension:	16-1/4"W x 19-1/4"H x 15-1/4"D
Weight:	16.25 lbs.
Safety tip-over switch:	Yes
Thermostat:	No
Oxygen depletion sensor (ODS):	No
Hose & regulator Included:	Yes
Fuel type:	Propane
Heat type:	Convection
High limit safety shut-off (HLS):	No
Ignition:	Piezo
Indoor safe:	No
Warranty:	1 Year
Approvals:	CSA/USA



CSA Certified

Always check local codes for permitted uses.

