



3/8" 70-Series LGX Chisel Chains Deliver Performance

SPECIFICATIONS

Chain Pitch	3/8"
Cutter Style	Chisel
Kickback Reduction	Ramped Depth Gauge
Sequence	LGX JGX
Recommended Bar Length	12-42" (30-107 cm)
Recommended Saw Sizes	Gasoline-powered 3-6 cu. in. (50-100 cc) and smaller saws
Recommended User	Commercial Professional

Long-lasting 70-series saw chain is designed for high performance, easy maintenance and loop consistency.

FEATURES	BENEFITS
Advanced grind geometry	<ul style="list-style-type: none"> Improved out-of-box grind High performance in all cutting modes Extreme cutting efficiency, less feed force required
Blued cutters	<ul style="list-style-type: none"> Superior corrosion resistance Base-cutter hardness consistency
Tumbled parts	<ul style="list-style-type: none"> Smooth finish Improved joint articulation, combats tight joints
Clean ground gullets	<ul style="list-style-type: none"> Increases chip flow, less chain clogging No out-of-the box filing needed
Skip Sequence	<ul style="list-style-type: none"> Professionals using longer bar lengths may prefer the full-skip 72JGX, 73JGX, and 75JGX options
	<ul style="list-style-type: none"> Helps keep oil where it's needed, on the chain Directs oil to the critical rivet flange/hole interface
	<ul style="list-style-type: none"> Top-plate witness mark makes accurate sharpening easier.
	<ul style="list-style-type: none"> Oregon® patented OCS-01 steel is designed to have long-lasting durability in the toughest conditions, including low temperatures
	<ul style="list-style-type: none"> Reduces vibration 25% or more at the handles

72LGX, 73LGX, and 75LGX Super Guard®



SHARPENING NOTES

- * When using an OREGON® file guide, ALWAYS hold it level, 0°, flat on the Top Plate



WARNING

Failure to follow filing instructions can increase the level of kickback which can result in severe injury to the saw operator or bystanders.

- Do not exceed the depth-gauge setting shown right.
- Always file depth gauges back to their original rounded or ramped shape after lowering.

ANSI KICKBACK CLASSIFICATION

72, 73, and 75LGX/JGX are yellow-label chains. Though these chains have ramped depth gauges which reduce kickback energies, these are NOT low-kickback chains. These chains should be used ONLY by individuals with experience and specialized training for dealing with kickback.

SHARPENING & GRINDING TOOL PART NUMBERS

	511AX 510A	31686	(12) 70502	5-3/4" Dia. OR 534-316A	(12) 12211	(10) 22290

SHARPENING & GRINDING ANGLES

	 7/32"	 25°	 10° *	 60°	 .025" / 0.6mm
	 3/16"	 25°	 10°	 55°	 .025" / 0.6mm

SAW CHAIN REPLACEMENT PARTS AND NUMBERS (25 PACKS)

72LGX/JGX	P26197	P26198	P23837	P23910	P65715
73LGX/JGX	P26197	P26198	P23837	P23910	P68183
75LGX/JGX	P26197	P26198	P23837	P23921	P30927

Replacement parts come in packs of 25

CHAIN GAUGE

	72LGX / JGX	73LGX / JGX	75LGX / JGX
	.050"	.058"	.063"

OREGON, Super Guard and Vibe-Ban are registered trademarks and LubriLink and Witness Mark are trademarks of Blount, Inc.

For more information on these and other OREGON® products, contact your authorized OREGON® distributor, or:

OREGON®, BLOUNT, INC. PO Box 22127 · Portland, OR, U.S.A. 97269-2127 Phone: 503-653-8881 Fax: 503-653-4201 Web: oregonchain.com

OREGON DISTRIBUTION LTD. 505 Edinburgh Rd. N., Guelph, Ontario, Canada N1H 6L4 Phone: 519-822-6870 Fax: 519-822-4999