

WIRING INSTRUCTIONS

TITLE

ELECTROMAGNETIC DRILL PRESS MOTORS

BULLETIN


MILWAUKEE ELECTRIC TOOL CORP. 13135 WEST LISBON RD. BROOKFIELD, WIS.

DATE
APRIL '89

58-01-0376

NOTE:

BE CAREFUL NOT TO PINCH WIRES WHEN SNAPPING WIRE TRAP IN PLACE.



WIRING SPECIFICATIONS

Wire No.	Wire Color	Origin or Gauge	Length	Terminals, Connectors and 1 or 2 End Wire Preparation
1	BLACK	FIELD	4-15/16"	STRIP 1/4" AND TIN.
2	YELLOW	FIELD	4-15/16"	STRIP 1/4" AND TIN.
3	RED	CORD	3-3/8"	STRIP 3/16" FOR T1.
4	BLUE	CORD	5"	STRIP 3/16" FOR T1.
5	BLACK	CORD	3"	STRIP 1/4" AND TIN.
6	WHITE	CORD	2-3/4"	STRIP 1/4" AND TIN.

NOTE:

All leads must be held to $\pm 1/8"$.
All field leads to be measured from and perpendicular to laminations.
All lead lengths are before stripping.

TERMINAL DESCRIPTION

Code	Part No.	Qty.
T1	23-74-0841	2
CONNECTOR DESCRIPTION		