

## Residential Power Washers

## Power Washers



2000 - 3000 psi - Model 006809-0  
(50-State CARB Compliant)  
UPC: 696471068092



\*Built in the USA using domestic and foreign parts

## FEATURES

### POWERFUL GENERAC OHV ENGINE

- Delivers maximum cleaning performance and reliability

### AXIAL CAM PUMP WITH EASY-ACCESS HOSE CONNECTIONS

- Prevents kneeling down on the ground

### ERGONOMIC SPRAY GUN

- Molded grip, easier-to-pull trigger, and rear hose connection for comfort during prolonged use

### OVERSIZED NEVER-FLAT TIRES

- Improved mobility on rugged terrain

### QUICK CLICK NOZZLE TIPS

- Easily change the intensity of the spray to suit the application

### COMPACT DESIGN

- Minimum storage space required in the garage or shed

### POWERDIAL™ VARIABLE PRESSURE CONTROL

- Adjust the spray intensity to meet a wide variety of cleaning tasks

# 2000 - 3000 psi

# Specifications

## PRESSURE AND FLOW

|                               |          |
|-------------------------------|----------|
| Max Outlet Pressure (psi/bar) | 3000/207 |
| Max Flow Rate (gpm)/(L/min)   | 2.5/9.5  |

## ENGINE

|                                    |                      |
|------------------------------------|----------------------|
| Manufacturer                       | Generac              |
| Displacement (in <sup>3</sup> /cc) | 12.9/212             |
| Type                               | OHV (Overhead Valve) |
| Orientation                        | Horizontal           |
| Low Oil Shutdown System            | No                   |
| Fuel Capacity (qt/L)               | 0.8/3                |
| Fuel On/Off Switch                 | Yes                  |
| Oil Capacity (oz/L)                | 20/0.6               |
| Recommended Engine Oil             | SAE 30 or 10W30      |
| Throttle Control                   | PowerDial™ / Manual  |
| Choke                              | Manual               |
| Starting Method                    | Manual/Recoil        |

## PUMP

|                                          |           |
|------------------------------------------|-----------|
| Type                                     | Axial cam |
| Maximum Water Supply Temperature (°F/°C) | 100/38    |

## HOSE

|                  |              |
|------------------|--------------|
| Length (ft/m)    | 25/7.6       |
| Diameter (in/mm) | .25/6.35     |
| Rating (psi/bar) | 3100/214     |
| Connectors       | M22 threaded |

## DETERGENT SYSTEM

|                      |             |
|----------------------|-------------|
| Chemical Description | Siphon hose |
|----------------------|-------------|

## NOZZLES

|                            |             |
|----------------------------|-------------|
| Number of Nozzles per Unit | 3           |
| Nozzle Descriptions        | 0, 25, Soap |

## GUN & LANCE

|                            |              |
|----------------------------|--------------|
| Gun Type                   | Ergonomic    |
| Gun to Lance Connection    | M22 Threaded |
| Gun to Hose Connection     | M22 Threaded |
| Lance Length (in/cm)       | 20/51        |
| Lance to Nozzle Connection | Quick change |

## FRAME & MISC.

|                    |                                 |
|--------------------|---------------------------------|
| Handle             | Folding                         |
| Frame Construction | Welded steel                    |
| Wheels (in/cm)     | 1.75 x 10/3.8 x 25.4 Never flat |

## DIMENSIONS & WEIGHTS

|                               |           |
|-------------------------------|-----------|
| Length (in/cm)                | 20.6/52.3 |
| Width (wheel to wheel, in/cm) | 18.5/47   |
| Height (in/cm)                | 39/99.1   |
| Unit Weight (lbs/kg)          | 68/30.8   |
| Boxed Length (in/cm)          | 22.4/56.9 |
| Boxed Width (in/cm)           | 20/50.8   |
| Boxed Height (in/cm)          | 23.1/58.7 |
| Boxed Weight (lb/kg)          | 76/34.5   |

## WARRANTY

|          |                |
|----------|----------------|
| Warranty | 2 year limited |
|----------|----------------|