

Stealth™ Series

Booth Filters & Tool Savers by



For use with air tools, sand blasting, sanding impacts, buffing; Ideal for mechanical section of body shop:



STEALTH 6900B • STEALTH 6910B

STEALTH 6950B • STEALTH 6960B

STEALTH 6952B • STEALTH 6962B

STEALTH 3050B • STEALTH 3060B

STEALTH 3052B • STEALTH 3062B

Perfect after-filters for desiccant dryers and as final paint air filter & control unit:

STEALTH 7000B • STEALTH 7030B
STEALTH 7800B



Ideal for paint booths, lacquer spraying, prep stations and protecting critical air tools:

STEALTH 6060B



Turn over
for details



Reading Technologies, Inc.

(800) 521-9200 www.rti-pbe.com

Removes:  

1.0 Micron • 60 scfm • Brass Manual Petcock Drain



1/4"
STEALTH 6900B No Regulator
STEALTH 6950B Regulator w/ Gauge
STEALTH 6952B Regulator w/ Gauge, (2) 1/4" Outlets

3/8"
STEALTH 3050B Regulator w/ Gauge
STEALTH 3052B Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element #: 6950-1

Removes:   

1.0 Micron • 60 scfm • Brass Manual Petcock Drain



1/4"
STEALTH 6910B No Regulator
STEALTH 6960B Regulator w/ Gauge
STEALTH 6962B Regulator w/ Gauge, (2) 1/4" Outlets

3/8"
STEALTH 3060B Regulator w/ Gauge
STEALTH 3062B Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element #: 6960-1

Removes: 

0.01 Micron • 60 scfm • Brass Manual Petcock Drain



1/4"
STEALTH 7000B Regulator w/ Gauge
STEALTH 7800B No Regulator

3/8"
STEALTH 7030B Regulator w/ Gauge

Replacement Element #: 3C-060

Removes:   

0.01 Micron • 60 scfm • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



1/4"
STEALTH 6060B Regulator w/ Gauge

Replacement Element #: 6960-1/3C-060

Note: All Stealth Units Feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F

Removal Key:  **Water**  **Dirt**  **Oil**



Reading Technologies, Inc.

(800) 521-9200 www.rti-pbe.com