




.325"

Faster in-the-cut performance and lower power consumption

SPECIFICATIONS

Chain Pitch



Cutter Style

Micro-Chisel®



Chain Gauge

.050"

Kickback

Reduction

Bumper Drive Link



Recommended

Bar Length

**13–18"
(33–46 cm)**



Recommended

Saw Sizes

**Gasoline-powered
2.2–3.5 cu. in.
(35–57 cc)**



Recommended

User

Consumer



Commercial



Professional



FEATURES

BENEFITS

Advanced grind geometry

- Enhanced grind geometry significantly improves out-of-box sharpness with substantial speed improvement in boring and bias (undercut) modes.

Bumper drive link

- Reduces kickback without sacrificing performance
- Meets ANSI B175.1 standards for low-kickback saw chain

Blued cutters

- Provide superior corrosion resistance and improved strength

Micro-Chisel® cutters

- Small-radius working corners that are fast-cutting and easy to maintain



Micro-Lite™

- When matched up with the ML, MG or MP OREGON® Micro-Lite™ guide bars, 95VPX chain provides increased cutting efficiency while requiring less power from the saw than standard cutting systems.



- Tie straps help keep oil where it's needed – on the chain



- Oil holes in the drive links help carry oil around the full length of the guide bar groove.



- Chassis design increases operators' comfort level by reducing vibration at the handles.



- Top-plate witness mark makes accurate sharpening easier.

SHARPENING NOTES

* When using an OREGON® file guide, ALWAYS hold it level, 0°, flat on the Top Plate



WARNING

This saw chain is low kickback chain. It met the reduced kickback requirements of ANSI B175.1 when tested on a representative sample of chain saws. Its safety features significantly reduce the hazard of kickback while maintaining high cutting performance.

ALL CUTTING CHAINS CAN KICK BACK, which may result in severe personal injury to the chain saw operator or bystanders. Operate your chain saw safely. Read all warnings in your chain saw operator's manual.

SHARPENING & GRINDING TOOL PART NUMBERS

	511AX 510A	31690	70503 (12)	5-3/4" Dia. OR 534-316	(12)	(10) 31941

SHARPENING & GRINDING ANGLES

	3/16"	30°	10°		.025" / 0.6mm
	3/16"	30°	10°	55°	.025" / 0.6mm

SAW CHAIN REPLACEMENT PARTS AND NUMBERS

95VPX	P101923	P101924	P100956	P101125	P111509	P101024

Replacement parts come in packs of 25

OREGON® and Micro-Chisel® are registered trademarks and, Lubriwell, LubriLink, Micro-Lite, Vibe-Ban and Witness Mark are trademarks of Blount, Inc. For more information on these and other Oregon® products, contact your authorized Oregon® distributor, or:

OREGON®, BLOUNT, INC. PO Box 22127 · Portland, OR, U.S.A. 97269-2127 Phone: 503-653-8881 Fax: 503-653-4201 Web: oregonchain.com
OREGON DISTRIBUTION LTD. 505 Edinburgh Rd. N., Guelph, Ontario, Canada N1H 6L4 Phone: 519-822-6870 Fax: 519-822-4999