# **Chicago Pneumatic**









People. Passion. Performance.

# CP7731/CP7732

### 3/8" and 1/2" Stubby Impact Wrenches

4.4 IN. - 112 MM ONLY

## ULTRA COMPACT & POWERFUL

- Mini-length: 4.4 in. - 112 mm

CP7731 - 3/8"

Max. torque: 306 ft-lbs. - 415 Nm

CP7732 - 1/2"

• Max. torque: 450 ft-lbs. - 610 Nm



#### **DIMENSIONS**

A	4	E	3	С				
in.	mm	in.	mm	in.	mm			
4.4	112	6.8	175	2.3	60			

#### **TUNE-UP KIT**

Description	Part number						
Tune-up kit	894 017 1649						



Model Part number	Anvil	Speed	Working torque		Max torque Weigh		ight	Length		Air cons. average		Air cons. @ load		Sound level	Vibration	Inner hose diameter in				
		inch	RPM	ft-lbs.	Nm	ft-lbs.	Nm	lbs	kg	inch	mm	cfm	l/min	cfm	l/min	dBA	m/s² (k)	in	mm	in
CP7731	894 107 7310	3/8	9,000	70-241	96-328	306	415	2.86	1,3	4.4	112	4.76	135	19.06	540	95	12.1 (4,4)	3/8	10	1/4
CP7732	894 107 7320	1/2	9,000	102-310	138-420	450	610	2.86	1,3	4.4	112	4.76	135	19.06	540	95	12.1 (4,4)	3/8	10	1/4

Listed specifications are for reference only. Please check tool documentation.



#### **SOCKETS**

SCAN THE QR CODE TO GO TO THE SOCKETS CATALOG

All sockets sizes and types available on **www.cp.com** 



#### PROTECTIVE COVER

Description Part number

Tool boot 894 017 2290



CP Mechanic Gloves offer ultimate comfort for the professional mechanic.

- 3 setting positions in

both directions

Chicago Pneumatic also offers a large range of air tools, accessories, and workshop equipment to optimize your air tools durability and performance: Check www.cp.com website for more information.



www.cp.com