



This powerful and high-quality 10 mm (3/8") drill is ideal for all general purpose drilling, honing, reaming and hole-sawing. With its reversible motor, it can also be used for removing screws, including backing out tight screws without struggle.

The planetary gear reduction balances the load on bearings and gears for increased tool life.

- ◆ Powerful 0.38 kW (0.5 HP) motor.
- ◆ 2 000 rpm free speed.
- ◆ Variable speed throttle for smooth operation and starting holes easily.
- ◆ Lightweight and compact drill for easy access.
- ◆ High-quality composite keyless chuck.

Specifications at 6.2 bar (90 PSI)

<i>Part number</i>	7802RAKC
<i>Ordering number</i>	80147424
<i>Chuck capacity</i>	3/8 in and 10 mm
<i>Also available:</i>	
- in none-reversible version with standard chuck:	7802A
- in none-reversible version with keyless chuck:	7802AKC
- in reversible version with standard chuck:	7802RA

PERFORMANCE

<i>Rated power</i>	0.5 hp / 0.38 kW
<i>Maximum free speed</i>	2 000 rpm

AIR SYSTEM

<i>Air inlet (NPTF)</i>	1/4 in
<i>Minimum hose size</i>	3/8 in / 10 mm
<i>Average air consumption</i>	4 cfm / 113 l/min
<i>Air consumption at load</i>	26 cfm / 736 l/min

NOISE & VIBRATIONS

<i>Sound pressure / power</i>	83.0 / 94.0 dB(A)
<i>Vibration level (ISO8662)</i>	0.4 m/s²

WEIGHT & DIMENSIONS

<i>Tool weight</i>	2.99 lb / 1.36 kg
<i>Tool dimensions (l x w x h)</i>	175 x 46 x 156 mm
<i>Shipping weight</i>	3.48 lb / 1.58 kg
<i>Shipping dimensions (l x w x h)</i>	180 x 240 x 60 mm
<i>UPC/EAN Code</i>	6 63023 01974 1