

FR250-G & FR500-G

Piggyback Filter & Filter Regulators



FR250-G



FR500-G

- 1/4" (FR250-G) or 1/2" (FR500-G)
- Adjustable 0-120 PSI regulator
- Filter/Regulator with glass face chrome gauge
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Filters to 5 micron
- Maximum pressure is 230 PSI (FR250-G) & 180 PSI (FR500-G)
- Temperature range from 40°F to 120°F
- 30 scfm (FR250-G) & 80 scfm (FR500-G) Rating

PROVIDES **CLEAN AIR** TO YOUR APPLICATIONS AT A **Low Cost!**



F250



F500

- 1/4" (F250) or 1/2" (F500)
- Low pressure drop
- Can be wall mounted or panel nut mounted
- Low cost, high efficiency design
- Semi-automatic drain with manual override
- Lightweight, high efficiency design is durable & rugged
- Filters to 5 micron
- Maximum pressure is 230 PSI (F250) & 180 PSI (F500)
- Temperature range from 40°F to 120°F
- 30 scfm (F250) & 80 scfm (F500) Rating

PERFECT FOR **DIY-ERS & SMALL SHOPS**

