

Features

- Forced opening line interrupter switch, requires machine restart in case of power failure or circuit interruption.
- Adjustable spindle tension return spring.
- Built-in laser pointer.
- Sturdy design with cast-iron head, base, and table.
- High-quality bearings for smooth, vibration-free operation.
- Simple hand lever controlled mechanical variable speed from 500 to 3000 rpm.
- Digital spindle speed display.
- 1/3 HP industrial-quality, 120 V motor.
- Equipped with easy to adjust dual depth stop for complete control of both down stroke depth and upstroke travel.
- 5/8" chuck with key & convenient onboard chuck key holder.
- Easy to use see-through flip-up chuck guard included.
- Crank-operated rack and pinion table height adjustment.

Optional accessories

- 22 piece drill set 1/16" to 3/8" (#70-020).
- 9" auger drill bit set (#70-105).
- Chuck guard (#70-115A).
- Self-centering pen drilling vise (#70-120).
- Drill press tool tray (#70-125).
- Chuck guard (#70-155).

#75-010 | 12" variable speed drill press



:: Click on image to enlarge ::

Swing	12" (305 mm)
Drilling capacity	5/8" (16 mm)
Chuck size	5/8" (16 mm)
Spindle travel	3 1/8" (80 mm)
Spindle distance to table	15" (380 mm)
Spindle distance to base	21 7/8" (556 mm)
Table size	9 1/2" x 9 1/2" (240 x 240 mm)
Column diameter	2 1/2" (65 mm)
Spindle speeds	(variable) 500 to 3000 rpm
Spindle	MT2
Overall height	33" (840 mm)
Base size	15" x 9 5/8" (380 x 245 mm)
Motor	1/3 HP, 120 V, 3.1 A
Weight	75 lbs (34 kg)

Manual

Print this page



► Line interrupter switch.