

## KEY FEATURES

- Solid steel body construction delivers maximum wear & protection

- Down-ward air exhaust



- Heavy duty twin hammer impact

- Variable Trigger



- Power regulator for easy adjustment



- Heat Treated Spherulitic iron cylinder ensure extended life



[www.EmaxCompressor.com](http://www.EmaxCompressor.com)  
1000 Cass Drive  
Clayton OH 45315  
Toll Free: 866-294-4153  
Fax: 937-540-1157



•Best product support and Limited Lifetime Warranty



EATIWH7S1P



EATIWH3S1P



EATIWC5S1P

Model#	EATIW05S1P	EATIWH5S1P	EATIWC5S1P	EATIWH7S1P	EATIWH3S1P
Impacts Per Min. (BPM)	1000	1320	1000	1450	1150
Avg. Air Consumption	7.1	7.1	7.1	7.7	3.8
Speed-no load (RPM)	7000	8000	7000	7500	9500
MAX. Torque (ft/Lbs)	450	560	425	1100	430
Air pressure (PSI)	90	90	90	90	90
Driver Size	1/2"	1/2"	1/2"	3/4"	3/8"
Housing	Aluminum	Aluminum	Composite	Aluminum	Aluminum
Decibel Rating (DBA)	95	100	91	100	100
Weight	5.72	5.72	4.62	6.16	3.23
DIMS (Inch)	8	7.28	7	8	6