

Eoslift

Eoslift Automation Technology Corp.

E20V

Scale Pallet Truck



Eoslift

Eoslift Automation Technology Corp.
No.99, Yanjia Road, Yuantong Town, Haiyan, Zhejiang
Province, China 314317
Tel: +86 573 8622 9999
Fax: +86 573 8622 2900
info@eoslift.com
www.eoslift.com

Hotline: 400-626-9090

Eoslift USA Corporation
1590 S.Milliken Avenue, Unit H, Ontario, California 91761
Tel: +1-888-264-5008
Fax: +1-781-780-5915
sales@eoslift.us
www.eoslift.us

Product features



High price–performance ratio

- Heavy-duty industrial grade products with entry-level cost
- Improve efficiency and simplify logistic processes
- Save time and space

Durability

- Dustproof and waterproof
 - Protection degree of gage outfit: IP53
 - Protection degree of sensor:IP67
- An iron cover added to the indicator to protect it from shock
- Compact indicator saves space, economic for transportation

Stable Structure

- The truck is designed with high-strength steel construction for durability
- Durable powder coat finish

Outstanding accuracy

- Filter is used to compensate for vibration and improves the measurement accuracy
- High accuracy, with maximum error: 0.05%

Low energy consumption

- Powered by 2×900mAh button cells
- Battery life: 300 operating hours (backlight off)

Convenience

- Easy-to-read backlit displays
- The indicator has four keys for easy operation
- Overload protection

Basic information		
Model	E20V	
Rated capacity	lb.	4400
Load center	in.	23.6
Service weight	lb.	286
size		
Wheel material	PU/NYLON	
Maximum error	%	0.05
Maximum fork height	<div>H</div> in.	7.5
Minimum fork height	<div>H1</div> in.	3
Steering wheel	in.	Φ7.1×2
Single Load-bearing wheel	in.	Φ2.9×3.7
Overall fork width	<div>B</div> in.	27
Fork length	<div>L</div> in.	48
Length of the truck	<div>L1</div> in.	65
Minimum turning radius	<div>R</div> in.	54.9
Type of battery	Button Cell	
Battery capacity	mAh	2×900

