



BBCV2.MH46579
Lithium Batteries - Component

[Page Bottom](#)

Lithium Batteries - Component

[See General Information for Lithium Batteries - Component](#)

QIXIN ADVANCED POWER SOURCE MATERIALS CO LTD

MH46579

SANLIQIAO
XINHUI RD
XINXIANG CITY, HENAN 453002 CHINA


Model No.	Secondary Type ^[d]	Max Charging Current (Ic), mA	Max Charging Voltage, V dc ^[e]	Test Compliance ^[f]
ICR14500	Lithium ion (Cylindrical)	800	4.2	1
ICR14650	Lithium ion (Cylindrical)	1100	4.2	2, 3
ICR18500 1300mAh	Lithium ion (Cylindrical)	1300	4.2	2, 3
ICR18500 1500mAh	Lithium ion (Cylindrical)	1500	4.2	1
ICR18650	Lithium ion (Cylindrical)	1800	4.2	1
ICR18650 2000mAh	Lithium ion (Cylindrical)	2000	4.2	1
ICR18650 2200mAh	Lithium ion (Cylindrical)	2200	4.2	1
ICR18650 2600mAh	Lithium ion (Cylindrical)	2600	4.2	1
ICR18650P, ICR18650PA	Lithium ion (Cylindrical)	1300	5	1
IFR18650P01, IFR18650PA01	Lithium ion (Cylindrical)	1200	4.3	1
IFR18650P02, IFR18650PA02	Lithium ion (Cylindrical)	1300	4.3	1
IFR22650P01, IFR22650PA01	Lithium ion (Cylindrical)	1500	4.3	1
IFR22650P02, IFR22650PA02	Lithium ion (Cylindrical)	1700	4.3	1
IFR26500P01, IFR26500PA01	Lithium ion (Cylindrical)	1500	4.3	1
IFR26500P02, IFR26500PA02	Lithium ion (Cylindrical)	1700	4.3	1
INR18650P	Lithium ion (Cylindrical)	1500	4.2	1

[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 - Complies with all single-cell tests
- 2 - Complies with all single-cell tests except the impact test
- 3 - Complies with all single-cell tests except the projectile test
- 4 - Complies with all single-cell tests except the crush test

Marking: Company name, Recognized Component Mark,  on the cell or smallest shipping package containing the cell.
[Last Updated](#) on 2013-06-19

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".