

GENERAL PRODUCT SPECIFICATION

Item No.	AW430				
Date	3-20-01	Replaces	7-12-99	No. Pages	1

T 1 4	T	
Product	Description:	
1 I Vuuct	DUSCHIDHUH.	

Style	SOC	
Item Size (each)	3"d x 48" long	
Color	Gray with black logo printing	
Composition	> 99% Polypropylene, < 1% Surfactant	
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)	
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)	
Technology	Meltblown + Spunbond + Sealed or Enclosed Ends	
Absorbency	Hydrophilic + Oleophilic	

Intended Application	Chemical Resistant "Universal" Sorbent Sock for Spills of Water Base, Oil	
	Base, or Solvent Base Liquids	

Absorbency Capacity	30 gal per bale (saturated; medium viscosity- 8.5x)
----------------------------	---

Packaging Description:

Package configuration	Case	Pkg. Weight	26-lbs
Items per Package	30 SOCS/Case	Pkg. Dimensions (approx.)	25.5"x 17"x 21"
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal Nominal	(+/-)Tolerance
SOC Weight	Gravimetric	lbs	0.8	0.2
Absorbency** (med.	SPCTM-012B	gL/gS	8.5	8-min.
oil)				
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
_	Date, and/or Package Code (Bar Code).
Certification Make no changes in basic process or composition without notifying cus	
	Claims for non-conformance of goods must be made within 60-days of delivery.