



MK-212 SERIES FEATURES

- · 2 HP direct drive motor
- · Plunge cut capability for scoring or cutting large tile
- Tilting head allows easy and precise 45° miter cuts
- Blade guard accommodates 10" profile wheels
- · Pivoting blade guard for easy blade changes
- Cutting head mounted on a roller-bearing carriage running on a stainless steel rail
- · 90° cutting guide for accurate material placement
- · Friction locks on both head height adjustment and carriage travel
- · Constructed with powder coated heavy-gauge sheet metal and cast aluminum components
- 1/4" thick rubber cutting surface
- · Built-in lifting handles for easy transport
- Built-in stand with removable legs
- · One year limited warranty



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158 www.mkdiamond.com | customerservice@mkdiamond.com









MK-212 Series Tile & Stone Saw

The MK-212 Professional Tile and Stone Saw is built rugged and portable for use on any jobsite. The powerful 2 HP direct drive motor is fully enclosed for greater protection. The adjustable built-in miter system allows cuts at all angles from 45° to 90°. The plunge cutting head has pivoting blade guard for easy blade changes. One-year limited warranty.

to 90°. The plunge cutting head has pivoting langes. One-year limited warranty.

Motor Electric

Power 2 HP 120V

Power	2 HP, 120V		
Model	MK-212-4	MK-212-6	
Blade Capacity	10" (254 mm)	12" (305 mm)	
Depth of Cut	2" (51 mm)	3" (76 mm)	
Length of Cut	36" (914 mm)	72" (1,829 mm)	
Diagonally Cut	24" (610 mm)	42" (1,067 mm)	
Depth of Cut at 45°	1-1/2" (38 mm)	2-1/2" (57 mm)	
L x W x H (inches) L x W x H (mm)	58" x 21" x 52" 1,473 x 533 x 1,321	82" x 21" x 52" 2,083 x 533 x 1,321	
Weight	226 lbs. (103 kg)	270 lbs. (122 kg)	
Includes	• Water Pump • Rip Guide • 12" Adjustable Cutting Guide	Water Pump Rip Guide 12" Adjustable Cutting Guide	
Part#	159414	167882	
·			

Optional	Side Table	Side Table	Transport
	(MK-212-4)	(MK-212-6)	Wheels
Part#	165884	167986	160172



Tilting head allows easy and precise 45° miter cuts



Optional transport wheels for easy transportation



90° cutting guide for accurate material placement

(Available with 220V/50Hz motor)