





MK-5005S

MK-5000 ELECTRIC SERIES FEATURES

- Precision screw feed mechanism allows the cutting head to be easily raised or lowered to the precise cutting depth required
- · Self-leveling blade guard provides optimum blade coverage for operator safety
- Open-back design allows for material up to 20" long to be cut
- Conveyor cart built from heavy-duty cast aluminum
- 3 phase saws are equipped with GE NEMA 1 starters in NEMA 12 enclosure
- Adjustable water supply for maximum blade protection
- · Built-in tie-downs for safer saw transport
- · Ergonomically designed handle for reduced operator fatigue
- Heavy-duty built-in forklift brackets allow lift to approach from the front or either side of the saw
- One-year limited warranty

Recommended Diamond Blades

MK-62GSPV Pro Granite Silent Core

Size	Part #			
14"	154591			
20"	155902			



MK-925DSLX Supreme Hard Material Silent Core

Size	Part #			
14"	161283			
20"	160971			





1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158 www.mkdiamond.com | customerservice@mkdiamond.com









MK-5000 Electric Series Wet Cutting Block Saws

The MK-5000 Series of block saws set the quality standard for durability and maintenance-free operation. These saws are specially designed to provide the highest level of productivity, operator safety and convenience. Heavy-duty cast aluminum and steel parts ensure the finest value in the masonry and stone industry. One-year limited warranty.

Motor Baldor (Electric)
Length of Cut 20" (508 mm)

L x W x H (inches) 53" x 26" x 63" L x W x H (mm) 1,346 x 660 x 1,600

> Includes • Electric Water Pump • Rip Guide

	The datas						
Model	MK-5005S		MK-5005T		MK-5007T		
Power	5 HP, 208-230V 1PH		5 HP, 230V 3PH 5 HP, 460V 3PH		7.5 HP, 230V 3PH 7.5 HP, 460V 3PH		
Weight	445 lbs. (202 kg) 451 lbs.		451 lbs. (205 kg)	(g) 485 lbs. (220 kg)			
	Blade Guard Options		Blade Guard Options		Blade Guard Options		
Size	14"	20"	14"	20"	14"	20"	24"
Depth of Cut	5" (127 mm)	8" (203 mm)	5" (127 mm)	8" (203 mm)	5" (127 mm)	8" (203 mm)	10" (254 mm)
208-230V Part#	160634-14	160634	160636-14	160636	160641-14	160641	160641-24
460V Part#	_	_	160637-14	160637	160642-14	160642	160642-24

(Motor available in other electrical configurations.)



Heavy-duty cast aluminum conveyor cart



Foot pedal for hands-free cutting head operation



Open-back design allow for materials up to 20" long to be cut