

DK2 CANADA 1080 Clay Avenue, Unit 2, Burlington, Ontario,

L7I OA1, Canada

DK2 USA 6245 Industrial Parkway Whitehouse, Ohio, 43571, United States





Detail K2 (DK2) believes in providing quality to our customers, delivering our products on time and in accordance with the ever changing needs of our clientele.

DK2 is committed to creating and maintaining powerful customer relationships built on a foundation of excellence. Our goal is to continuously bring to market innovative automotive and truck accessory products which effortlessly improve and shape the future.

We believe that our business can - and should - have a positive impact on the communities we serve. Whether it's Snow Plows, Winches, Trailers or any other products we sell, at Detail K2 we are focused on making our business and yours more efficient, sustainable and inviting than ever before.

LIMITED 1 YEAR WARRANTY

WHAT IS COVERED

DK2 Inc. warrants to the original purchaser of any DK2 product that it will be free and clear of manufacturing defects in workmanship and materials under normal use and service for a period of one (1) year from the date of the original purchase.

If within one (1) year from the original date of purchase this product fails due to defect in material or workmanship, Detail K2 will repair, replace, or supply any defective part at our option. Upon expiry of one (1) year, Detail K2 will have no further liability related to the product. Detail K2 does not authorize any party, including its authorized distributors or dealers, to offer any other warranty on behalf of Detail K2 Inc.

THIS WARRANTY DOES NOT COVER OR APPLY TO:

- (a) Damage to the product due to misuse, mishandling and abuse
- (b) Improper installation, maintenance and storage
- (c) Expendable parts such as nuts and bolts, pins and springs
- (d) Normal wear and tear
- (e) Consequential damage & incidental damages such as damage to persons or property

PROCEDURE FOR OBTAINING A RETURN AUTHORIZATION

Within the one (1) year warranty period, the purchaser of the product must notify an authorized distributor or dealer of the claimed defect and provide proof of original purchase. At this time the validity of the claim will be determined and a Return Goods Authorization Number (RGA) will be issued if approved. No returned product will be accepted under warranty unless accompanied by an RGA# issued by Detail K2 Inc.

RESOLUTION FOR A DEFECTIVE PRODUCT

Detail K2 Inc. will at its option repair or replace the defective product covered by this warranty. The repaired product will be shipped to the purchaser upon completion. All transportation charges shall be the responsibility of the purchaser. Any damage in transit will be the responsibility of the carrier or at the risk of the purchaser.

	Multi Utility Trailer4-5
-	Galvanized Utility Trailer 6-7
	Mini Utility Trailer8-9
OH).	Portable Battery Boosters10-11
	Flip Rack12
All I	Hitch-mounted Motorcycle Carrier13
	Cargo Carrier 14-15
L	Hitch Mounted Bike Racks 16-17
DATE TO	Snow Plows 18-21
	Snow Plow Accessories22-23
	DK2 Warrior Winches24-37
	Winching Accessories38-39





Truly the ultimate 1.500lb trailer available on the market today. This trailer is unique in its versatility and functionality. When the front and back load-bearing gates are in the down position, the bed of the trailer extends to nearly 12 feet. Fabricated from 100% steel, all of the components are reinforced, adjustable, removable, and /or interchangeable, making this trailer the clear choice and one of the best values in the market today.



tube cambered axle with 30.5 cm (12 in.) 6 ply bias tires, and a load capacity of 1,639 lb (743.4kg). When the front and back load-bearing gates are down, the trailer bed extends to nearly 3.5 m (11.58 ft.). Another great feature is the tilt/ dump capability that makes it easy to load or unload heavy items. Fabricated from 100% steel, all of the components are reinforced, adjustable, removable and / or interchangeable.

SPECIFICATION

GVW: Curb weight 451 lb. 204.6 kg Payload capacity 1,639 lb. 743.4 kg 52 x 88 to 52 x 136 inches Bed dimensions 1.32 x 2.24 to 1.32 x 3.45 m

177 in. 4.50m tongue extended

Overall length Floor height Construction

Side panels Drop gates Lighting

14 in. H 35.6 cm H Corrugated steel 24 in. H 61 cm H Corrugated Trailer comes pre wired with quick connect LED lighting. Complies with DOT requirements. Adjustable rear light protectors and protected side markers.

Fully welded tubular steel frame

(hot dipped galvanized available)

Dump bed 2 position 16 in. 40.6 cm Hitch height Flooring

100% steel corrugated welded reinforced bed

20 in. 50.8 cm

Assembly time Carton dimensions

60 minutes approx. 88.5 x 55 x 8 inches (DWH) 224.79 x 139.7 x 20.32cm

Also available hot dipped galvanized.









MIGHTY MULTI UTILITY TRAILER

DK2's legendary 5-in-1 Utility Trailer

Item Number: MMT5X7

- Back drop gate
- 100% Steel
- Heavy duty
- Best in Class
- Exclusive Design • Extended bed length: nearly
- 12 feet / 3.66 metres.
- 2 position dump bed
- Quick release lock pin Load bearing gates
- Removable steel side panels
- Corrugated steel floor
- 100% welded tubular
- steel frame • Heavy-duty tail light
- protectors
- Solid square tube cambered axle
- Easy-lube 5 on 4.5 hub assembly
- V tongue for added strength
- 2" coupler with safety chains
- 12 x 5.3 6 ply bias tires
- UPC 826518003391











The newest member of the DK2 trailer line up is the Hot Dipped Galvanized 5 x 7 Utility Trailer. The MMT5X7G is fully welded and hot dipped galvanized to protect the steel from the elements especially in coastal regions.



Coming 2018 the newest member of the DK2 trailer line up is

2,090 lb. 948.0 kg

451 lb. 204.6 kg

20 in. 50.8 cm

2 position

16 in. 40.6 cm

reinforced bed

60 minutes approx.

1,639 lb. 743.4 kg

52 x 88 to 52 x 136 inches

1.32 x 2.24 to 1.32 x 3.45 m

Fully welded hot dipped

with DOT requirements.

177 in. 4.50m tongue extended

galvanized tubular steel frame

24 in. H 61 cm H Corrugated

14 in. H 35.6 cm H Corrugated steel

Trailer comes pre wired with quick

connect LED lighting. Complies

Adjustable rear light protectors and protected side markers

100% steel corrugated welded

224.79 x 139.7 x 20.32cm (DWH)

88.5 x 55 x 8 inches (DWH)

DESCRIPTION

SPECIFICATION

GVW:

Curb weight

Payload capacity

Bed dimensions

Overall length

Floor height

Construction

Side panels

Drop gates

Dump bed Hitch height

Assembly time

Carton dimensions

Flooring

Lighting

Item Number: MMT5X7G

TRAILER

FEATURES

GALVANIZED MIGHTY MULTI UTILITY TRAILER

DK2's legendary trailer just got hot dipped galvanized!


- Best in Class
- Extended bed length: nearly 12' / 3.66 metres.

- Load bearing gates
- panels
- steel frame
- Heavy-duty tail light
- Solid square tube
- Easy-lube 5 on 4.5 hub assembly
- V tongue for added
- 2" coupler with safety chains





Ships in a single



- 2 position dump bed
- Quick release lock pin
- Removable steel side
- Corrugated steel floor
- 100% welded tubular
- protectors
- cambered axle
- strenath
- 12 x 5.3 6 ply bias tires
- UPC 826518004848









The DK2 MMT4X6 single axle 1.2m x 1.8m (4ft. x 6ft.) trailer is the perfect solution for anyone needing to pull a trailer behind a small vehicle, full size, lawn tractors or ATVs. This trailer is engineered to provide exceptional balance & ease of mobility with a load capacity of 587.4 kg (1,295 lb.). It is made from 100% welded tubular steel with expanded steel decks. The back gate is multi-purpose and can sit flat in the bed, up in a vertical position or lying down as a ramp for easy loading.



DESCRIPTION

The "little brother" of the best-selling DK2 MMT5X7 is specially designed for handling a variety of hauling tasks. This trailer is the perfect solution for anyone needing to pull a trailer behind a small vehicle, full size truck, law tractor, or ATV.

The trailers are engineered to provide exceptional balance and ease of mobility without giving up one ounce of payload capacity. Every trailer is made from 100% welded tubular steel with expanded steel decks. Our back gate design is multi-purpose and can sit flat in the bed, up in a vertical position, or lying down as a ramp for easy loading.

SPECIFICATION

GVW: 1,600 lb. 725.7 kg
Curb weight 305 lb. 138.3 kg
Payload capacity 1,295 lb. 587.4 kg
Bed dimensions 48 x 72 inches
1.21 x 1.82 m

Overall length
Floor height
Construction
Side panels

152 in. 3.86m tongue extended
18 in. 45.7 cm
Fully welded HD tubular steel
Solid Sides

Floating Ramp Gate 36 in. Reinforced square tube steel ramp with heavy duty

round tube exterior

Trailer comes pre wired with quick connect LED lighting. Complies

with DOT requirements.
Adjustable rear light protectors and protected side markers.

Hitch height 14 in. 35.5 cm

Lighting

Flooring 100% welded down corrugated steel floor panel

Shine in a Stack

MIGHTY MINI UTILITY TRAILER

The 'little brother' of the MMT5X7 - Perfect for those smaller hauls!

Item Number: MMT4X6

- Capacity: 587.4 kg (1,295 lb.)
- Fully welded heavy-duty powder-coated steel frame
- Corrugated steel floor & solid side and front panels/rails
- Solid square tube cambered
- Drive up rear ramp tailgate
- 2 position dump bed axle mount with quick release lock pin
- Hitch height: 40.6 cm (16 in.)
- Heavy-duty tail light protectors
- LED quick connect lighting with side markers
- Wheel diameter: 12"
- Wheel bolt pattern: 5 on 4-1/2"
- Tire size: 4.80-12
- Load range: C
- Assembly required
- 17/8" coupler
- UPC 826518004831







New to the DK2 family is the GL10 Portable Battery Booster. This unit is industry leading in every way and can provide a portable emergency power source when you need it most.

The GL10 comes with intelligent clamps that fit both 12V and 24V car jump starters. There is intelligent detection circuit which can tell the output voltage of 12V and 24V car jump starter, and start different protection system accordingly. The unit also has a warning sound and LED light reminder.

Overall protection functions include: back charge protection, overcharge protection, over discharge protection, shortage protection and reverse polarity protection, as well as function of testing the situation of the cars battery.





HEAVY DUTY PORTABLE BATTERY BOOSTER PACK

Item Number: GL10

ACCESSORIES

- Starting Power Bank
- Home Charger
- Micro Cable
- Jump Cable Battery Clamps
- 12 V Output Converter
- 24 V Output Converter
- User Manual
- Carrying Bag

TECHNICAL SPECS

- Battery Capacity: 88.8 Wh
- Start Current: 400 A
- Peak Current: 800 A
- Input: 15 V / 2 A
- Output: 5 V / 2 A, 12 V / 24 V for Jump Start
- Charging Time: 4.5 Hours
- Life Time: > 800 Cycles
- \bullet Size: 7" L x 2.5" W x 2.5" H
- Weight: 1040g





The DK2 Power 2 Go is the incredibly powerful yet versatile battery jump starter that literally sits in the palm of your hand.

Slightly larger than your Smartphone, it is powerful enough to jumpstart most full sized cars and trucks. All this power and it can still be easily

stored in your glove box. With multiple ports and adapters included, there's no longer a need to panic when your Smartphone, tablet or

laptop is running low on power. Simply plug into your DK2 Power 2 Go and watch in amazement as your device quickly charges.

The P2G can be used on: Cars, Bobcats, ATV's, UTV's, Snow-mobiles, Golf carts, and Boats.





POWER 2 GO PORTABLE BATTERY CHARGER

Item Number: P2G850

FEATURES

- Built in rechargeable high output Lithium-iron battery
- 14,000 mAh capacity
- Upgraded Copper Booster cables and clamps
- Output: 12V / 5V, 2 A
- Peak Current 400A
- 850 Cold Cranking amps starting current
- Can boost a single vehicle 20 times on a single charge
- Overload and over-charge protection
- Charging adapters for most major electronic devices

TECHNICAL SPECS

- Item Number: P2G850
- Unit Dimensions: 6.3 x 3.0 x 1.4"
- Assembled Weight: 2 lbs
- Gross Weight: 3 lbs
- Box Dimensions: 11 x 2 x 8"
- UPC: 826518005142





HITCH-MOUNTED MOTORCYCLE CARRIER

Mounts to any 2" hitch receiver

Item Number: TMC201

DESCRIPTION

How to determine weight capacity

To determine the weight capacity for the Detail K2 Hitch Mounted Motorcycle Carrier, you must first determine the tongue weight limit of your hitch receiver AND the tongue weight limit of your vehicle. Take the lesser of these two figures and see the chart opposite:

Hitch / Vehicle Tongue Weight Limit (use lowest figure)		Max. Carrying Capacity of K2 Carrier	
300 lb.	136 kg	180 lb. 82 kg	
350 lb.	159 kg	225 lb.	102 kg
500 lb.	227 kg.	350 lb.	159 kg
750 lb.	340 kg	450 lb.	204 kg

Example 1 If you have an SUV with a hitch receiver max. tongue weight of 500 lbs, AND your SUV manufacturer states that the maximum tongue weight for your vehicle is 500 lbs, then the maximum weight you can load on the Detail K2 Hitch Mounted Motorcycle Carrier is 350 lbs.

Example 2 If you have an SUV with a hitch receiver max. tongue weight of 500 lbs, BUT your SUV manufacturer states that the maximum tongue weight for your vehicle is only 350 lbs, then the maximum weight you can load on the Carrier is 225 lbs.



FEATURES

- Extremely versatile, Extremely secure and stable: patent-pending design results in snug, "antiwobble" fit.
- Tilts down to allow easy loading: one-person operation
- Easily installed and removed: no extra tools required
- Ideally suited for SUV, RV, or pickup truck with cap
- Features adjustable front wheel channel (to accommodate different sized bikes) and retractable tie-down bar
- Comes with safety chains and hitch pin
- Fits standard 2-" class III or IV hitch receiver: weight capacity dependent on receiver strength
- Black UV powder-coat finish
- UPC: 693495970561





DK2 FLIP RACK

Easy, no drilling installation

Item Number: TFR150

DESCRIPTION

The TFR150 give you flexibility and combines the safety and security of a headache rack with the functionality of an elevated ladder rack. Installation takes minutes, requires no drilling and fits most full size trucks.

With a simple flip up and back of the crossbar the rack immediately gives you the ability to transport everyday things that require extra length. Ladders, pipe, lumber and even canoes all easily tie down fixed and secure on the upper deck. Once you're done the crossbar is easily flipped forward and down and secured back to its starting position against the headache rack.

AVAILABLE ACCESSORIES

- Light Bar
- Boat Rack
- Adaptor Kit for Hard Top Tonneau Covers



- Converts from a window guard into a full-length utility rack with a simple "flip" of a crossbar
- Strong and rigid: heavy-duty steel construction
- Cargo can be secured to window guard to prevent shifting loads
- Rack can support up to 225 kg / 500 lbs (distributed) in open position: ladders. lumber, etc.
- Easily installed and removed
- No drilling truck (clamps provided)
- Fits most makes and model trucks
- Pkg. dim.: 54.0 x 24.0 x 5 inches (1372 x 610 x 127 mm)
- Gross weight: 121.25 lb. (55 kg)
- Minimum bed width is 51 inches
- UPC: 693495970721





HITCH MOUNTED CARGO CARRIER

Mounts to any 2" hitch receiver

Item Number: **HCC602**

DESCRIPTION

Increase the cargo capacity of your vehicle or haul bulky, messy items like luggage, coolers or firewood. Easy assembly. Conveniently mounts to any 2" hitch receiver on cars, SUVs, trucks, or vans.



Flips up when not in use, and stows up against the rear of the vehicle.



FEATURES

- Black powder-coat finish resists corrosion.
- Carrying capacity dependent on receiver strength: 500 lb. (226.8 kg) when used with a Class III / IV hitch.
- Heavy-duty tubular and expanded steel mesh construction.
- Mounts to any 2" hitch receiver.
- Conveniently flips up when not in use.
- Ships unassembled.
- Dimensions: 60 x 20 x 6 inches $(152.4 \times 50.8 \times 15.2 \text{ cm}).$
- Assembled weight: 59.5 lb. (27
- UPC: 827518001165





ALUMINIUM HITCH MOUNTED CARGO CARRIER

Mounts to any 2" hitch receiver

Item Number: HCC502A

DESCRIPTION

The DK2 Hitch Mounted Aluminum Cargo Carrier allows you to immediately increase the cargo capacity of your vehicle so you can haul bulky, messy items like luggage, coolers or firewood. This functional item has a 500lb carrying capacity and also flips up close to your vehicle when not in use. The aluminum construction is lightweight while still being durable and rust proof.



Packaged Product:

• Height: 4 Inches

• Width: 50 Inches

• Weight: 32 Lbs

Depth: 24 Inches

TECHNICAL SPECS

Assembled Product:

- Height: 6.5 Inches
- Width: 49.5 Inches
- Depth: 22.25 Inches
- Weight: 29 lbs.

- Increase The Cargo Capacity Of Your Vehicle.
- Easy Assembly.
- Mounts To Any 2 in. Hitch Receiver.
- Flips Up When Not In Use: Stows Against Rear Of Vehicle.
- Aluminum Finish Resists Corrosion.
- Includes threaded anti-wobble hitch pin for added stability.
- Carrying Capacity Dependent On Receiver Strength.
- Ships Unassembled.
- Reflectors for added safety.
- UPC: 826518005051





HITCH MOUNTED BIKE CARRIER

Mounts to any 2" hitch receiver

Item Number: BCR390

DESCRIPTION

Family holidays are always better when you take the bikes along too. Detail K2 offers two different hitch mounted bike racks to do just that. Carry up to 4 bicycles easily.



Three different positions allow you to minimize distance bike carrier extends while also being able to swing the unit away and access the rear of your vehicle.



FEATURES

- Carries up to 4 bikes with easy to mount system
- Cradles padded with rubber to protect bike finish
- Cradle bar folds down when not in use
- Unit swings down for access to the rear of the vehicle
- Steel construction
- Black powder coat finish resists scratches and corrosion
- Slides into a standard 2" hitch receiver
- Anti-wobble hitch pin secures unit to hitch
- Shipped unassembled
- Full colour carton
- Pkg. dim.: 36 x 11 x 6 inches (914 x 279 x 152 mm)
- Gross weight: 26 lb. (11.7 kg)
- UPC: 826518004879





HITCH MOUNTED BIKE CARRIER

Mounts to any 2" hitch receiver

Item Number: BCR490

DESCRIPTION

Family holidays are always better when you take the bikes along too. Detail K2 offers two different hitch mounted bike racks to do just that. Carry up to 4 bicycles easily.



Three different positions allow you to minimize distance bike carrier extends while also being able to swing the unit away and access the rear of your vehicle.



- Carries up to four bicycles on individually adjustable cradles
- Padded no-mark cradles with dual bike retention straps
- Cradle bar folds down when not in use
- Carries up to 4 bicycles on adjustable saddles
- Saddle bar folds down when not in use
- Unit swings down for access to the rear of vehicle
- Steel construction
- Black powder coat finish resists scratches and corrosion
- Slides into a standard 2" hitch receiver, Class III or IV (optional 1-1/4" adaptor kit available upon request)
- Shipped unassembled
- Weight: 44 lb. (19.96 kg)
- UPC: 827518001172





All DK2 Snow Plows allow you to quickly & effectively remove snow from your driveway or small parking lot. DK2's range of personal plows each mount on to a vehicle specific custom mounting brackets. Ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a 3,000lb wireless electric winch.

- Fits most light trucks and SUV's
- Easy to mount simply slides onto vour custom vehicle specific mounting brackets in seconds. Slide out and roll away
- An electric winch lifts the blade. controlled from inside your warm vehicle for easy up and down snow
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- · Powder coated all-steel construction with UV protected paint
- · Locking castors allow easy plow attachment, removal, and roll away storage - just lower the wheels and roll the unit to wherever you want it
- ISO 9001 certified manufacturer
- 1 year limited warranty
- Ships in a single carton on a standard size pallet







DESCRIPTION

Our brand new DK2 Avalanche Snow Plow kits combine the simplicity of our original T-Frame plow with the strength of our custom mount

The DK2 Avalanche Snow Plow allows you to guickly and effectively remove snow from your driveway or small parking lot. The Avalanche simply slides into a 2" front mount receiver for easy removal and storage.

Each snow plow ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a 3,000lb wireless electric winch. Each Avalanche plow will also include a set of blade stiffeners for added strength by creating a 3 point connection.



ACCESSORIES

Light kit and replacement

parts available for purchase.

Plow Stiffeners

Included

SPECIFICATION

- Item Number: AVAL8219
- Blade Dimensions: 82 x 19 Inches H
- Assembled Weight: 265 lbs
- Gross Weight: 321 lbs
- Box Dimensions: 46 x 36 x 18 Inches
- UPC: 826518004992

• Item Number: AVAL8422

- Blade Dimensions: 84 x 22 inches H
- Assembled Weight: 283 lbs
- Gross Weight: 334 lbs
- Box Dimensions: 44 x 32 x 18 inches
- UPC:826518005005

AVALANCHE SNOW PLOW

Universal Mount

Item Numbers: **AVAL8219 AVAL8422**

FEATURES

- Fits most light trucks and SUV's
- Easy to mount simply slides into a 2" class III front mount receiver in seconds. Slide out and roll away for storage
- An electric winch lifts the blade. controlled from inside your warm vehicle for easy up and down snow control
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- Powder coated all-steel with UV protected paint
- Flip down locking castors allow easy plow attachment, removal, and roll away storage - just lower the wheels and roll the unit to wherever you want it
- Each snow plow kit also includes a set of blade stiffeners for added strength
- ISO 9001 certified manufacturer
- 1 year limited warranty





for storage







SNOW PLOWS

CUSTOM MOUNT SNOW PLOW KITS

Wireless Winch

SUMMIT II 88x26" SNOW PLOW

Item Number: SUMM8826

- Blade Dimensions: 88 x 26 inches
- Assembled Weight: 296 lbs
- Gross Weight: 341 lbs
- Box Dimensions: 46 x 35 x 17 inches
- Custom mount sold separately
- UPC: 693495992181

STORM II 84x22" SNOW PLOW

Item Number: STOR8422

- Blade Dimensions: 84 x 22 inches
- Assembled Weight: 283 lbs
- Gross Weight: 325 lbs
- Box Dimensions: 44 x 32 x 18 inches
- Custom mount sold separately
- UPC: 693495992174

RAMPAGE II 82x19" SNOW PLOW

Item Number: RAMP8219

- Blade Dimensions: 82 x 19 inches
- Assembled Weight: 265 lbs
- Gross Weight: 315 lbs
- Box Dimensions: 43 x 32 x 18 inches
- Custom mount sold separately
- UPC: 693495992167



DESCRIPTION

Dk2's line of personal snow plows just got better! The DK2 ELITE SERIES Snow Plow line up takes its simple yet effective design and improves on it with a wireless actuator for ultimate reliability.

DK2's ELITE SERIES each mount on to a vehicle specific custom mounting brackets. Each snow plow ships in a single carton complete with hardened steel cutting edge scraper, rubber snow deflector, polymer-wrapped wire rope plow markers, skid shoes, castor kit for easy storage, and a wireless electric actuator kit.

FEATURES

- Fits most light trucks and SUV's
- Easy to mount simply slides onto your custom vehicle specific mounting brackets in seconds. Slide out and roll away for storage
- An electric actuator lifts the blade, controlled from inside your warm vehicle for easy up and down snow control
- Blade angles set and lock manually with a single lever lifting a pin to 3 blade locking positions: straight on, angled to the right, and angled to the left
- Powder coated all-steel construction with UV protected paint
- Locking castors allow easy plow attachment, removal, and roll away storage - just lower the wheels and roll the unit to wherever you want it
- ISO 9001 certified manufacturer
- 1 year limited warranty
- Ships in a single carton on a standard size pallet



CUSTOM MOUNT SNOW PLOW KITS

Wireless Actuator

SUMMIT II ELITE 88x26" SNOW PLOW



STORM II ELITE 84x22" SNOW PLOW



RAMPAGE II ELITE 82x19" SNOW PLOW





ACCESSORIES

LIGHTING



More Snow Plow Accessories

Item No	Description	UPC
AF6	A Frame	6 93495 99258 7
DFS	D Frame	6 93495 99259 4
CH55	Chain	6 93495 99278 5
WCB	Winch Control Box	8 26518 00312 4
RC17	Receiver	6 93495 98004 1
MF	Main Frame	8 26518 00353 7
PSB-2	1st Gen Support Bracket (2)	8 26518 00456 5
88RB	88" Right Blade	6 93495 99005 7

Item No	Description	UPC
88LB	88" Left Blade	6 93495 98007 2
84RB	84" Right Blade	8 26518 00347 6
84LB	84" Left Blade	8 26518 00348 3
82RB	82" Right Blade	8 26518 00349 1
82LB	82" Left Blade	8 26518 00350 6
FR7-2	Frame Pin(2/box)	6 93495 99279 2
CP21	Clevis pin	6 93495 99277 8
HEATSYNC	Heat Sync Cable	6 93495 99022 4

Universal Steel Skid Shoes



- Qty: 2
- Item No: SS2600
- UPC: 6 93495 99262 4

Replacement Winch Strap



- Item No: WS8020
- UPC: 6 93495 99282 2

Wireless Winch Remote



- wireless connection to the winch SW2300 Swivel- 6 93495 99261 7 SPR108488EYE- 84/88"
- UPC: 6 93495 97026 4

Universal Plow Markers



- Qty: 2
- Item No: PM2700
- UPC: 6 93495 99263 1

Scraper Blades



- SB8200 82" 6 93495 99269 3
- SB8410 84" 6 93495 99270 9 • SB8820 - 88" - 6 93495 99271 6

Replacement Castor Wheel



- Simple key fob design with no-fuss
 CW2300- Rigid- 6 93495 99260 0
 SPR1082EYE- 82"- 6 93495 97042 4

Replacement Winch



- Item No: EW8020
- UPC: 6 93495 97027 1

Snow Deflector rubber only



- RUB82 82" 6 93495 99272 3
- RUB84 84" 6 93495 99273 0
- RUB88 88" 6 93495 99274 7

Replacement Springs



- 6 93495 97043 1

Snow Plow Lighting

All kits come with bull moose style mounting bar.

LED Spot Work Light Kit

PART NUMBER 81256LB2

- Long life LED reduces maintenance costs and downtime.
- Solid state design for reliable operation in all conditions
- 24 LED Spot Pattern
- Operating voltage: 12 V DC
- Weight: 1.5 lb. (0.68 kg) each
- PDM housings with bracket
- Lumens: 400

STORM II

• UPC: 8 26518 00305 6

Standard Plow Halogen Light Kit

PART NUMBER 83026LB2

- Polymer housing & glass lens
- Includes 2 lamps with H3 bulbs, bracket, switch, relay & harness
- Reversible mount
- Operating voltage / current / power: 12 V DC, 4.6 A, 55 W
- Dimensions (LWH): 2.3" x 5.4" x 3.1" (58 x 137 x 79 mm)
- UPC: 8 26518 00307 0

Halogen Snow Plow Light with Turn Signals

PART NUMBER 814882




- Pre-wired with high beam, low beam and turn signal
- Operating voltage: 12 Vdc
- Application: forward lighting
- Glass lens
- Includes brtacket and wiring harness
- UPC: 058205814885

22 23

DEG







Features

DK2 WARRIOR WINCHES

In the most extreme conditions, when lesser products might be found wanting, DK2 Warrior Winches will deliver what your customer demands and our service levels will raise the bar in the process.

Whatever the requirement and whatever the vehicle we can supply a DK2 Warrior Winch that will provide exceptional performance and be backed by only the highest level of customer service and after sales support thus our motto" Value Without Compromise".

Value for money specification



At Detail K2 Inc. we recognize that our customers want an all-inclusive price and do not want the bother of searching through a long, expensive extras list. It's for this reason that each one of our Winches is supplied as standard, with a specification that translates into exceptional value for your hard earned money.

Highest quality motors are the powerhouse, 3 stage Planetary Gears provide the right ratios for any task. Our water resistant solenoids and fully sealed housings deliver reliability in the field regardless of what Mother Nature throws your way.

Limited Lifetime Warranty



It shouldn't come as a surprise that every DK2 Warrior Winch is backed by a no quibble Limited Lifetime Warranty. We are so confident in our product that in the unlikely event something should go wrong there will be a simple and direct commitment to rectifying the problem. It's this integrity that translates into knowing our service and reputation will deliver when called on.

A 1 year warranty if offered for commercial and industrial applications. For more warranty information please visit our website at www.detailk2.com





Ideal for large ATV's and small trailers. A huge high power motor, heavy duty clutch, heavy duty steel gearing and heavy duty waterproof contactors ensure the ultimate in performance and reliability. Strengthened Steel drum makes it ideal to use with Synthetic Rope.

Watertight 4 Pin connection allows the use of 'Plug and Play' Wireless.

NNJAI

C3500N, C3500N-SR

FEATURES

- Sealed High Power Motor
- Heavy Duty Watertight Contactors
- Full Steel Planetary Gearing
- Watertight Controller Socket

Synthetic version available

- Strengthened Steel Drum (suitable for Synthetic rope)
- Gloss Chip Resistant Paint

SPECIFICATION

C2500N

2500lbs(1134kg) RATED LINE PULL: MOTOR: 12v: 1.35hp / 0.95kw **GEARING:** 170:1 BRAKING ACTION: Dynamic

DRUM SIZE Dia x L: 1.5×3.1 " CABLE Dia x L: 0.2" x 46 ft **MOUNT PATTERN:** 3.1"

13.2 x 4.4 x 6.5" **DIMENSIONS:**

C3500N

RATED LINE PULL: 3500lbs (1588kg) MOTOR: 12v: 1.95hp / 1.37kw **GEARING:** 170:1

BRAKING ACTION: Dynamic **DRUM SIZE Dia** x L: 1.5×3.1 " CABLE Dia x L: 0.2" x 42 ft **MOUNT PATTERN:** 3.1" **DIMENSIONS:** 13.7 x 4.6 x 6.5"

NINJA SERIES ATV WINCHES

Item Numbers: C2500N, C2500N-SR

INCLUDED

- Steel Cable
- Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- 3 Tonne Pulley Block
- Mounting plate & Hardware
- 1/4 hook





High quality three stage planetary gearing ensure this is one of the quietest and smoothest winches on the market.

The silky smooth performance and the full load holding brake make it the perfect solution for high spec applications.



available

SPECIFICATION

RATED LINE PULL: 4500lbs (2041kg) MOTOR: 12v: 1.95hp / 1.37kw **GEARING:** 172:1 **BRAKING ACTION:** Auto in the drum

DRUM SIZE Dia x L: 1.7 × 3.8" 0.25" x 47.5ft CABLE Dia x L: **MOUNT PATTERN:** 5 × 3.7" **DIMENSIONS:** 144 x 49 x 64" **WEIGHT:** 28.6 lbs

Layer of	Line pull
wire rope	lbs (kg)
1	4500 (2401)
2	3642 (1652)
3	3060 (1388)
4	2638 (1196)

Line pull	Line speed		peed Amp d	
lbs (kg)	ft/min	m/min	12v	24v
0	11.6	3.6	20	15
1500 (680)	9.2	2.8	70	40
2500 (1134)	7.8	2.4	100	65
3500 (1587)	6.6	2.0	140	80
4500 (2041)	4.9	1.5	200	130

NWA

NINJA SERIES TRAILER WINCHES

Item Numbers: C4500N C4500N-SR

FEATURES

- Power in and Power out
- High Torque 1.95hp Motor
- HD Waterproof Contactors
- Full Steel Planetary Gearing
- Mount Plate as Standard
- Full Load Holding Break
- Can fit tow ball mount

INCLUDED

- 0.25" x 47.5ft Steel Cable
- 3m Remote Handset
- · Heavy Duty Roller Fairlead
- Heavy Duty Battery Leads
- Mounting plate
- Mounting hardware
- 3/8 hook
- *ATV remote available









Warrior Winches are delighted to announce the arrival of the new member of Spartan Series, Tough, Strong and ready for Battle. The Spartan 6000 Lb short drum model is ideal where space and payload are limited. The winch has a short drum and is less than 66Lbs, however the extended drum supports allow it to carrier up to 131ft of 0.28" cable. The Synthetic rope version comes fitted with 0.27" x 98ft.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

With great performance, outstanding features included as standard. & backed by the Warrior Winches un-rivalled limited Lifetime Warranty, this should make a Spartan the first choice for all serious enthusiasts.

SPECIFICATION

RATED LINE PULL: 6000 lbs (2727kg) MOTOR: 12V: 4.5hp / 3.4kW **GEARING:** 230:1 **DRUM SIZE Dia x L:** 2.48 × 4.2" 0.28" x 131' CABLE Dia x L: 17.4 x 7.7 x 10.8"

DIMENSIONS: WEIGHT: 66 lbs

Layer of wire rope	Line Pull lbs (kg)	Cable Cap ff (m)
1	6000 (2727)	9.8 (3.0)
2	4979 (2258)	22.0 (6.7)
3	4255 (1930)	36.1 (11.0)
4	3714 (1685)	52.2 (15.9)
5	3296 (1495)	70.5 (21.5)
6	2962 (1344)	90.9 (27.7)
7	2690 (1220)	113.2 (34.5)
8	2463 (1117)	131.2 (40.0)



Steel Cable version available

Line pull	Line speed		Amps
lbs (kg)	ft/min	m/min	12v
0	19.4	5.9	80
2000 (907)	13.1	1.0	140
4000 (1814)	9.2	2.8	210
6000 (2727)	7.2	2.2	285

SPARTAN

SPARTAN 6000 **ELECTRIC WINCH**

Item Numbers: 6000 6000-SR

FEATURES

- Weather Sealed High Performance
- Heavy Duty 3 Stage Gearbox
- Heavy Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch is 100% Load Tested
- Chip Resistant Gloss Paint Finish

INCLUDED

- 10ft Remote Handset
- 5/16 Hook
- Aluminium or Roller Fairlead (Synthetic rope or steel cable)
- Heavy Duty Battery Leads
- Stainless Steel Mounting Hardware
- 0.27" x 98ft Synthetic Rope or 0.28" x 131ft Steel Cable







DESCRIPTION

We are delighted to announce the arrival of the Spartan Series, Tough, Strong and ready for a Battle, these Winches really will challenge all before them. We have reluctantly termed them as 'entry level', however this describes the price point, not the performance.

We really believe these to be the best value for money Winches around, a lower price does not mean that we have had to compromise the core values integral to a good winch, such as reliability and durability.

SPECIFICATION

8000

RATED LINE PULL: MOTOR: 12v: **GEARING: BRAKING ACTION:** DRUM SIZE Dia x L: CABLE Dia x L: **MOUNT PATTERN: DIMENSIONS:**

8000lbs(3629kg) 4.6hp / 3.2kw 233:1 Auto in the drum 2.5 x 8.8"

0.3" x 85 ft 10 x 4.5" 21.3 x 6.3 x 8.6"

12000

RATED LINE PULL: MOTOR: 12v: **GEARING: BRAKING ACTION: DRUM SIZE Dia x L:** 2.5 × 8.8" CABLE Dia x L: **MOUNT PATTERN: DIMENSIONS:**

9500lbs(4500ka) 4.6hp / 3.2kw 230:1

Auto in the drum 0.36" x 82 ft 10 x 4.5" 21.3 x 6.3 x 8.6"

9500

12000lbs (5400kg) 6.0hp / 4.6kw 230:1 Auto in the drum 2.5 x 8.8" 0.4" x 82 ft 10 x 4.5"22.8 x 6.3 x 8.6"

Synthetic versions

available



SPARTAN SERIES **ELECTRIC WINCH**

Item Numbers: 8000, 8000-SR 9500, 9500-SR 12000, 12000-SR

FEATURES

- Weather Sealed High Performance
- Heavy-Duty 3 Stage Gearbox
- Heavy-Duty Drum Supports
- Weather Sealed Solenoids
- Full Steel Planetary Gearing
- Full Load Holding Brake
- Every winch 100 % load tested
- Chip Resistant Gloss Paint Finish

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Steel Roller Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- Clevis hook







Superb high specification winch. Ideal for recovery and 4x4 applications. Outstanding features include high quality series wound double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing.

Comes with stainless steel roller fairlead and fittings as standard. Complete with Heavy Duty integrated wireless remote. Available with Armortek Synthetic Rope and Aluminum Fairlead.



Synthetic version available

SPECIFICATION

S8000

RATED LINE PULL: 8000lbs(3629kg) 9500lbs(4500kg) MOTOR: 12v: 4.6hp / 3.2kw **GEARING:** 210:1 BRAKING ACTION: Auto in the drum Auto in the drum

DRUM SIZE Dia x L: 2.5 x 8.8" CABLE Dia x L: **MOUN PATTERN: DIMENSIONS:**

S9500

4.6hp / 3.2kw 230:1

2.5 x 8.8" 0.3" x 95 ft 0.4" x 85 ft 10 x 4.5" 10 x 4.5" 21.3 x 6.3 x 8.6" 21.3 x 6.3 x 8.6"

S12000

RATED LINE PULL: 12000lbs(5400kg) MOTOR: 12v: 6.5hp / 4.6kw **GEARING:** 230:1

BRAKING ACTION: Auto in the drum **DRUM SIZE Dia x L:** 2.5 x 8.8" CABLE Dia x L: **MOUNT PATTERN:** 10 x 4.5" **DIMENSIONS:**

0.4" x 85 ft 22.8 x 6.3 x 8.6"

SANIURAK

SAMURAI SERIES **ELECTRIC WINCH**

Item Numbers: S8000, S8000-SR \$9500, \$9500-SR, S12000, S12000-SR

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

INCLUDED

- Galvanized steel cable
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook



WINCHES



DESCRIPTION

SPECIFICATION

Line pull

lbs (kg)

9500

(4309)

7706

(3495)

6482

(2940)

5400

(2400)

RATED LINE PULL:

BRAKING ACTION:

DRUM SIZE Dia x L:

MOUNT PATTERN:

CABLE Dia x L:

DIMENSIONS:

Layer of

wire rope

2

3

4

MOTOR: 12v:

GEARING:

The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing.

9500lbs(4500kg)

Auto in the drum

22.7 x 6.3 x 8.5"

Line pull

lbs (kg)

0

4000

(1818)

6000

(2722)

9500

(4309)

6.5hp / 4.5kw

110:1

2.5 x 8.8"

10 x 4.5"

0.4" x 98 ft

Complete with heavy duty integrated wireless remote. Available with Steel Rope or Armortek Synthetic Rope and Aluminum Fairlead.



Steel Cable version available

Amp draw

24v

45

175

230

335

12v

80

300

400

530

Line speed

m/min

19.8

3.8

3.6

1.9

ft/min

65

12.5

11.81

8.86

FEATURES

Item Numbers:

S9500HS-SR

S9500HS

• All Brass (no corrosion) Series Wound Motor

SAWURAL

PERFORMANCE WINCH

SAMURAI 9,500 LB

HIGH SPEED

- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Integrated Wireless Remote

INCLUDED

- Wire rope 0.4" x 98ft
- 10ft Remote Handset
- Roller Fairlead (does not attach to winch)
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook







The narrow drum version of the best selling 9500. A total width of 17.2 inches ensures this is the perfect product for limited space. The 5.0hp motor delivers 9500lb of pulling power in space normally designed for Winches with half the power.

The Short Drum winch is the preferred choice of the British Military on specialist vehicles currently serving in action. Available with synthetic rope and aluminium fairlead, to give a total weight of 44 lbs.

Steel Cable version available

SPECIFICATION

RATED LINE PULL: 9500lbs(4500kg) **MOTOR: 12v:** 5.0hp / 3.5kw **GEARING:** 230:1

EARING. 230

BRAKING ACTION: Auto in the drum **DRUM SIZE Dia x L:** 2.5 x 4.7"

CABLE Dia x L: 0.4" x 46 ft

MOUNT PATTERN: 5.9 x 4.5"

DIMENSIONS: 17.2 x 6.3 x 10.7"

Layer of	Line pull
wire rope	lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5593 (2537)

Line pull	Line speed		Amp	draw
lbs (kg)	ft/min	m/min	12v	24v
0	23	7	80	70
3000 (1361)	12.5	3.8	170	140
6000 (2722)	9.8	3	260	210
9500 (4309)	6.4	1.9	380	270

SAWURAK

SAMURAI 9,500 LB SHORT DRUM WINCH

Item Numbers: S9500SD S9500SD-SR

FEATURES

- Power in and Power out
- High Quality 5.0hp Series Wound Motor
- Heavy Duty Waterproof Contactors
- Full Steel Planetary Gearing
- Double sealed motor and drum
- Full Load Holding Brake
- Integrated Wireless remote

INCLUDED

- 0.4" x 46ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook







DESCRIPTION

Warrior Winches are excited to announce the arrival of the colossal Samurai 17500 & 20000lb Winches. Designed for the toughest of applications & tested in the most extreme environments imaginable, these Winches boasts a massive 7.0 & 7.5 hp Series wound motors respectively.

Double sealed drum on maintenance free bearings and quiet, fully sealed efficient full steel planetary gearing ensures these immense Warriors are ready for any battle.

SPECIFICATION

S17500 Winch

RATED LINE PULL: 17 500lbs (7938kg) **MOTOR: 12v:** 7.0hp / 4.9kw **GEARING:** 430:1

BRAKING ACTION: Auto in the drum
DRUM SIZE Dia x L: 3.5 x 8.6"

 CABLE Dia x L:
 0.5" x 85 ft

 MOUNT PATTERN:
 10 x 4.5"

 DIMENSIONS:
 24 x 8.5 x 10"

 WEIGHT:
 147.7 lbs

\$20000 Winch

RATED LINE PULL: 20 000lbs (9072kg) **MOTOR: 12v:** 7.5hp / 5.4kw

GEARING: 430:1

BRAKING ACTION: Automatic in the drum

 DRUM SIZE Dia x L:
 3.5×8.6 "

 CABLE Dia x L:
 0.47" $\times 87$ ft

 MOUNT PATTERN:
 10×4.5 "

 DIMENSIONS:
 $24 \times 8.6 \times 10.7$ "

 WEIGHT:
 158.7 lbs

SANIURAK

SAMURAI 17500 & 20000 LBS WINCHES

Item Numbers: \$17500 \$20000

FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Reinforced Plastic Contactor Cover
- Double Sealed Drum (G-box/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- High Quality Steel Drum Supports

INCLUDED

- 0.5" x 85ft Wire Rope
- 10ft Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Wireless Remote





The Predator is designed for hard-core competition. Two powerful 7.2HP sealed motors provide a performance that is truly out of this World, coupling this with a 108:1 ratio 3 stage planetary gearbox enables this performance winch to handle even the most extreme offroad punishment.

With a surprisingly low draw of only 140 amps (at no load), the Predator also contains an innovative "multi stop" 10% ratchet brake design, which provides zero drag when returning the "cable in", and is situated away from the drum to prevent any damaging heat transferring to your Armortek or Synthetic rope.

The steel drum flanges are precision machined to 0.39" on either side to resist the unique loading characteristics of synthetic rope, while the Alloy Carbon gears are heat treated and tempered to 62HRc rating for extra strength. This Warrior from another dimension will mercilessly prey on its weaker rivals, hunting the opposition down. At 10kg lighter than any of its nearest competitors, with off-load line speeds from 65ft per minute & available with or without synthetic rope, there's a Predator out there, ready & waiting, for everyone!

SPECIFICATION

RATED LINE PULL: 10 000lbs (4536kg)

MOTOR: 12v: 7.2hp / 5.4kw

 GEARING:
 108:1

 DRUM SIZE Dia x L:
 2.8 x 8.42"

 CABLE Dia x L:
 0.35" x 124ft

 MOUNT PATTERN:
 10 x 4.5"

DIMENSIONS: 18.8 x 10.3 x 13.9"

WEIGHT: 99lbs

Layer of wire rope	Line pull lbs (kg)	Total Rope on drum ft(m)
1	10000 (4536)	18.4 (5.6)
2	8153 (3698)	41.0 (12.5)
3	6881 (3131)	68.9 (21)
4	5953 (2700)	101 (30.8)
5	5245 (2379)	131.2 (40)

Line pull	Line speed	Amp draw
lbs (kg)	ft(m)/min 12v	12v
0	66 (20)	140
4000 (1816)	19.7 (6.0)	400
6000 (2722)	16.7 (5.1)	560
8000 (3629)	13.1 (4.0)	690
10000 (4536)	10.5 (3.2)	790

PREDAT R

PREDATOR 10,000 LB
DUAL MOTOR
PERFORMANCE WINCH

Item Number: P10000D-SR

FEATURES

- Dual 7.2HP (5.4KW) Sealed Motors
- Sealed Motor conforms to IP67
- Sealed Waterproof Contactor
- "Multi Stop" 10% Ratchet Brake Design
- Sealed 3 Stage Planetary Gears
- Alloy Carbon Gears hardened to 62HRc Rating
- No load speed of 65ft/min

INCLUDED

- 0.35" x 124ft Synthetic Armortek Rope
- Wireless remote with LCD Display
- Heavy Duty Remote Control
- Silver Warrior Aluminum Fairlead
- Heavy Duty Battery Leads
- Stainless Steel Mounting hardware
- 12 Ton Competition Hook







DESCRIPTION

Compact, tough. A hydraulic winch for industrial and commercial applications. The unique patented steel gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding. Stainless steel roller fairleads and fittings are standard.

SPECIFICATION

10 000 NH HYDRAULIC Winch

 RATED LINE PULL:
 10 000lbs (4536kg)

 MAX LINE PULL:
 12 500lbs (5670kg)

 MOTOR:
 Hydraulic Dis 50 ml/r

 GEARING:
 33:1

 GEARING:
 33:1

 DRUM SIZE Dia x L:
 2.8 x 8.8"

 CABLE Dia x L:
 0.4" x 87ft

 MOUNT PATTERN:
 10 x 4.5"

 DIMENSIONS:
 20 x 7.3 x 8.8"

15 000 NH HYDRAULIC Winch

 RATED LINE PULL:
 15 000lbs (6804kg)

 MAX LINE PULL:
 17 000lbs (7711kg)

 MOTOR:
 Hydraulic Dis 80 ml/r

 GEARING:
 37:1

 GEARING:
 37.1

 DRUM SIZE Dia x L:
 3.5 x 8.8"

 CABLE Dia x L:
 0.5 x 87ft

 MOUNT PATTERN:
 10 x 4.5"

 DIMENSIONS:
 20.9 x 8.1 x 9.7"



NH SERIES
HYDRAULIC
WINCHES

Item Numbers: 10000NH 15000NH

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Stainless Steel fairlead and Fittings
- Rugged and compact for Long Life

INCLUDED

- Steel cable (see below)
- Heavy Duty Roller Fairlead (10000/15000NH)
- 5/16 or 3/8 Hook







Compact, tough. A hydraulic winch for industrial and commercial applications. The special heat treated planetary gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range.

Complete with internal brake to ensure maximum control and load holding.



NW SERIES HYDRAULIC WINCHES

Item Numbers: 10000NW 15000NW

FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Rugged and Compact for Long Life
- Meets the requirements of SAE J706



DESCRIPTION

Tough and compact, the JP series are heavy duty hydraulic winches designed and tested for toughest applications.

Minimum rope to drum ratio of 10:1, multi disc frictional brake, balance valve and rope tensioner as standard.

Available from 10 tonne to 40 tonne. Manufactured to meet GJB82-86 National Military Standard.



JP SERIES **HYDRAULIC** WINCHES

Item Numbers: 10TJP, 13.5TJP, 15TJP 20TJP, 30TJP, 40TJP

FEATURES

- Full Float Heavy Duty Planetary Gearing
- Multi Disc Friction Brake
- Minimum 10:1 Rope/Drum Ratio
- High Torque Industrial Motor
- Air and Manual Clutch Operation

SPECIFICATION

10 000 NW Winch

RATED LINE PULL: 10 000lbs (4536kg) MAX LINE PULL: 12 500lbs (5670kg) MOTOR: Hvdraulic Dis 100.8 ml/r **GEARING:**

DRUM SIZE Dia x L: 3.9 × 9.9" 1/2" x 86 ft CABLE Dia x L:

14.6 × 4.5" (11.34 × 4.5") **MOUNTING: DIMENSIONS:** 25 x 10.33 x 9.39"

15 000 NW Winch

RATED LINE PULL: 15000lbs(6810kg) MAX LINE PULL: 17 500lbs (7954kg) MOTOR: Hydraulic Dis 160 ml/r **GEARING:** 17.2:1

DRUM SIZE Dia x L: 5 x 10.6" CABLE Dia x L: 0.6" x 92 ft 11.9 x 4.5" (14.5 x 4.6") **MOUNTING:**

DIMENSIONS: 28.2 x 11.1 x 12"

INCLUDED

• 86 ft x 1/2" steel cable

WWW.DETAILK2.COM

- 5/16 Hook
- Tensioner included

SPECIFICATION

RATED LINE PULL (btm layer): 10 000 kg

22046 lbs **WORKING SPEED** (btm layer): 21.6ft/min* **ARRESTER RESP PRESS:** 5 Mpa **WORKING PRESSURE: OIL FLOW:**

DRUM SIZE: REC ROPE SIZE:

WEIGHT:

20 Mpa 15-75 L/min 5.4x12.4" 157ft x 0.6" 363 lbs

10TJP

20TJP

650 lbs

RATED LINE PULL (btm layer): 20 000 kg 44092 lbs **WORKING SPEED** (btm layer): 20ft/min **ARRESTER RESP PRESS:** <2.5 Mpa **WORKING PRESSURE:** 17 Mpa **OIL FLOW:** 120 L/min **DRUM SIZE: REC ROPE SIZE:** 197ft x 1"

WEIGHT: *when oil flow 60L/min

13.5TJP 15TJP

13 500 kg 15 000 kg 29762 lbs 33069 lbs 24.6ft/min 20ft/min <2.5 Mpa <2.5 Mpa 17 Mpa 17 Mpa 110 L/min 110 L/min 15.7x8.3x13.4" 15.7x8.3x13.4" 131ft x 0.7" 230ft x 0.9" 578 lbs 628 lbs

9UTOE 40TJP

30 000 kg 40 000 ka 66138 lbs 88184 lbs 18ft/min 10ft/min <2.5 Mpa <2.5 Mpa 17 Mpa 17 Mpa 120 L/min 120 L/min 20.9x8.3x13.4" 20.9x11x14.2" 23.7x11x18.9" 197ft x 1.3" 213ft x 1.4" 1257 lbs 1763 lbs

INCLUDED

- Heavy Duty Rope Tensioner as Standard
- Balance Valve as Standard





AMORTEK WINCH ROPE

Armortek synthetic rope is 70% stronger than wire!

- Armortek weighs 6 times less than wire
- Unlike wire, Armortek will not whiplash if broken.
- Armortek is rated at 70% stronger than wire. • Armortek floats, wire doesn't.
- · Armortek is coated to prevent abrasion.
- You don't have to worry about wire splinters.

Diameter	6mm (3/16")	9.5mm (3/8")
Breaking	3200 kg	7500 kg
Load	(7040 Lb)	(16500 Lb)

Part no: HW0884-CAD: 6mm x 16m (1/4" X 50') Synthetic Rope Part no: HW0932/45-CAD: 10mm x 14m (3/8"x 45") Synthetic Rope Part no: HW0932/85-CAD: 10mm x 26m (3/8" x 85') Synthetic Rope

CENTURION WIRELESS REMOTE



The ultimate remote for the professional user.

- Two-way Closelink wireless communication. Distinct source code so no interference from other remotes in the vicinity.
- Centurion devices are perfectly watertight. Output protection from short circuits &
- surges. Manufactured in highly resistant moulded
- plastic with a rubber shell for protection. The absence of mechanical elements enables functioning in unfavourable environments, with a temperature range from -20°C to

Part no: CENT12/242FCT - Centurion Remote



ROLLER FAIRLEAD

ROLLER FAIRLEAD



Part No: RFF400-CAD Part No: RFS150-CAD Chrome 4 Way Roller Fairlead For Stainless Fairlead With Hole Winches Up to 4500 lb. Centres 255mm

ALUMINIUM FAIRLEADS

+55°C.



ALI450-CAD - 2500/3500 Winch . ALXT450-CAD - 4500 XT Winch.

ALUMINIUM FAIRLEADS



ALI950-CAD - 9500SD Winch. ALI015-CAD - 8000/9500/12000 Winch

8T PULLY BLOCK

HOOK & RELEASE PIN

CHK014-CAD - 1/4 Steel Hook CHK038-CAD - 3/8 Steel Hook CHK516-CAD - 5/16 Steel Hook

2T PULLY BLOCK



Part No: PBK300-CAD 2 Tonne Pully Block Hook Type.

4T PULLY BLOCK



Part No: PBK900-CAD 4 Tonne Swingway Pully Block.

Part No: PBK150-CAD 8 Tonne Swingway Pully Block.

WINCH KIT WINCH KIT PRO



Part No: AWK001-CAD Warrior Bag, 1m Strop, 1/4 Shackle, 4T Pulley Block.



Part No: LWK001-CAD Warrior bag, 2m Strop, Gloves, 4.75 Shackle, 8T Pulley Block.

WINCH COVER SMALL



Part No: SWC001-CAD ATV Small Winch Cover



WINCH COVER

Part No: LWC003-CAD Winch Cover For Heavy Duty Winches up to 13000lbs.

SHACKLES



TREE STROP

SHK325-CAD - 3.25 Tonne Shackle. Part No: STP002-CAD SHK475-CAD - 4.75 Tonne Shackle. 2m x 60mm - 14 Tonne tree strop.



Part No: RWS001-CAD Rubber removable winch stopper.

INSTALLATION PLATE

WINCH STOPPER



Part No: PWM001-CAD Portable bumper.

Part No: IST200-CAD

Winch installation plate for

WIRELESS REMOTE

Wireless Remote Control With Key

Winches up to 20 000lb.

PORTABLE BUMPER

INSTALLATION PLATE

INSTALLATION PLATE



WIRED REMOTE

Part No: IST900-CAD Winch installation plate for Winches up to 9 000lb.

Part No: HRO001-CAD

Part No: EWX001-CAD

Control / NO Socket

Heavy Duty Wireless Remote

Wired Remote

Toggle (WARN Type) Hand Held

WIRELESS REMOTE

INSTALLATION PLATE

Part No: IST500-CAD Winch installation plate for 9500 SD Winches

Part No: HRO002-CAD

Series (air socket).

WIRED REMOTE

WIRELESS REMOTE

Part No: IST600-CAD Winch installation plate for Winches up to 15 000lb

ATV HANDLEBAR REMOTE



Hand held remote for XT and A



ATV / Quad Handlebar Remote.

Fob Handset / Air Socket. **ATV CONNECTOR**

Part No: CPW001-CAD

WIRELESS REMOTE



Part No: EWX002-CAD Heavy Duty Wireless Remote Control with Socket



Part No: EWX003-CAD Wireless Remote Control for XT and A series (Air Socket)



Part No: AIRS01-CAD ATV to Standard Socket Connector

Y CABLE





Part No: AIRS02-CAD Y Cable For Dual Connection.



SOLENOID SET

Part No: ATC012-CAD



Solenoid Set For Up to 4500lbs Winch.

WINCH UPGRADE KIT



ISOLATION SWITCH

Part No: BATOO1-CAD Battery Isolation Switch.



EXTENSION SOCKET

Part No: EXTO01-CAD Solenoid Box Extension Socket.



Part No: CON012-CAD 12v Heavy Duty Contactor.



Part No: AUKOO1-CAD Universal 12v Winch Upgrade Kit & Mini Thumbswitch.



SNAP CONNECTOR

Part No. QCC400-CAD 400 amp Snap Connector.



6.5 HP 12V MOTOR

Part No: EPW012-CAD 6.5 HP 12v Motor.



DK2 CANADA 1080 Clay Avenue, Unit 2, Burlington, Ontario, L7l 0A1 , Canada DK2 USA 6245 Industrial Parkway Whitehouse, Ohio, 43571, United States

TEL: 1-888-277-6960 WWW.DETAILK2.COM