Featuring Our New Series Of 10 in. Table Saws

Fence & Rail Systems





36-T30T3 & 36-T50T3
T-Square Fences



BC30-T2 & BC50-T2

BIESEMEYER® T-Square Fences Kit

BIESEMEYER

ACCESSORIES

For Pre-2008 Unisaws & Contractor Saws



34-154 Standard Insert Rt Tilt Saws Only

36-861

Standard Insert

Lt Tilt Saws Only



34-264 Dado Insert Rt Tilt Saws Only



36-847 Dado Insert Lt Tilt Saws Only



34-868 Disappearing Splitter Rt Tilt Unisaw Only



36-862 Zero Clearance Insert Rt/ Lt Tilt Saws



50-273 Mobile Base Unisaw/ HDSHPR



50-284 Mobile Base Ext. 52 in. Unisaw

About DELTA

With more than 90 years of Delta design knowledge and innovation, Delta has introduced to the market a new table saw. This table saw, backed by the heritage of a company known for its long lived dependability is an example of Delta's commitment to the woodworker and their precision projects. This and the commitment of the state of the art manufacturing and testing labs means Delta is here to continue their long-standing position in woodworking and power tool design.



©2014 Delta Power Equipment





The Measure of Precision™



° Max Rip: 30 in. RH & 15 in. LH





- ° Push Button Arbor Lock Easy Blade Changes
- ° BIESEMEYER® Fence System

UNISAWS

BIESEMEYER

BIESEMEYER



78-9450 Outfeed Tab

A DELTA

POWER EQUIPMENT CORPORATION

36-805

Zero Clearance Table Insert



78-970 Jnisaw Accessory Drawer



36-808

Zero Clearance Insert

For Dado Blades

ACCESSORIES

78-967 Thin Kerf Riving Knife

° Table Size: 20 in. x 27 in. (50 in. x 27 in. With Wings)

° Induction Motor: 15 Amp, 120V-240V, 1 Phase, 60 Hz

° Max Depth Of Cut: 3 1/2 in. @ 90° & 2 1/4 in. @ 45°

° Cast Iron Table With 1-LH & 2-RH Stamped Steel Wings

36-5000





° Induction Motor: 15 Amp, 120V-240V, 1 Phase, 60 Hz

° Max Depth Of Cut: 3 1/2 in. @ 90° & 2 1/4 in. @ 45°

° Cast Iron Table, 2 Steel Wings & Laminated Ext. Board

° Table Size: 20 in. x 27 in. (40 in. x 27 in. With Steel Wings)

(76 1/2 in. x 27 in. With Laminated Board)

° Max Rip: 52 in. RH & 15 in. LH

36-5100

- ° Induction Motor: 15 Amp, 120V-240V, 1 Phase, 60 Hz
- ° Max Rip: 30 in. RH & 15 in. LH
- ° Max Depth Of Cut: 3 1/2 in. @ 90° & 2 1/4 in. @ 45°
- ° 2 Cast Iron Wings & 1-RH Stamped Steel Wing
- ° Table Size: 20 in. x 27 in. (50 in. x 27 in. With Wings)

36-L336

- ° Motor: 3 HP, 230V, 1 Phase, 60 Hz
- ° Max Rip: 36 in. RH & 13 1/2 in. LH
- ° Cast Iron Table & Wings (31 in. x 40 in.)
- ° With Laminated Table Board (31 in. x 64 in.)

Blade Diameter: 10 in. Blade Speed 4,300 RPM Depth of Cut at 45°: 2 1/8 in. & 3 1/8 in. @ 90° Table Height: 35 in. Chip Exhaust Opening: 4 in. & 5 in.



50-257 Mobile Base For Saw 52 in. Fences



36-501 Zero Clearance Throat Plate



36-502 Dado Table Insert





36-5052

- 36-L552PH3K ° Motor: 5 HP, 230V, 3 Phase, 60 Hz
- 36-L552PH3M
- ° Motor: 5 HP, 460V, 3 Phase, 60 Hz
- 36-L552PH3L
- ° Motor: 5 HP, 200V, 3 Phase, 60 Hz Chip Exhaust Opening: 4 in. & 5 in.

36-L352

- ° Motor: 3 HP, 230V, 1 Phase, 60 Hz
- ° Max Rip: 52 in. RH & 13 1/2 in. LH
- ° Cast Iron Table & Wings (31 in. x 40 in.)
- With Laminated Table Board (31 in. x 82 in.)

36-L552

Blade Diameter: 10 in.

Table Height: 35 in.

Blade Speed 4,300 RPM

- ° Motor: 5 HP, 230V, 1 Phase, 60 Hz
- ° Max Rip: 52 in. RH & 13 1/2 in. LH
- ° Cast Iron Table & Wings (31 in. x 40 in.)
- ° With Laminated Table Board (31 in. x 82 in.)



34-184 Universal Tenoning Jig



34-976 Uniquard Over Arm Blade Guard



34-929 Deluxe Miter Gauge



36-5152

- ° Induction Motor: 15 Amp, 120V-240V, 1 Phase, 60 Hz
- ° Max Rip: 52 in. RH & 15 in. LH
- ° Max Depth Of Cut: 3 1/2 in. @ 90° & 2 1/4 in. @ 45°
- ° Cast Iron Table, 2 Cast Iron Wings & Laminated Ext. Board
- ° Table Size: 20 in. x 27 in. (40 in. x 27 in. Cast Iron Wings) (76 1/2 in. x 27 in. With Laminated Board)



- ° Cast Iron Table Top
- ° Heavy Duty 1-Piece Rail System
- ° Heavy Duty T-Square Fence

10 in. TABLE SAWS

